

# CP-30/CP-30Z

# CHART PROJECTOR

**SIMPLE OPERATION AND ECONOMY PRICE**

**VARIABLE FOCUS REFRACTING DISTANCE BY CP-30Z**

## FEATURES

Random chart or mask selection with wireless switch provides quick inspections.

Wide-range inspections with 22 charts and 12 masks.

Energy saving with automatic power off function after approx. 10 minutes idling.

Bright and uniform projection by halogen lamp.

4 different transmitting frequencies are available for combination use of two or more units.

## SPECIFICATIONS

Main Unit Specifications		Switch-Box Specifications	
Number of charts	22 charts and 12 masks	Control	Wireless remote control (4 wavelengths available)
Tilting angle	5° upward, 5° downward	Lamp	ON/OFF switch provided
Auto power off	After 10 min.	Power Source	UM-4 batteriesX2
Lamp	12V, 30W halogen lamp	Dimensions	180mm(L)X60mm(W)X18mm(H)
Power Source	85V~132V, 170V~264V	Weight	110g
Power consumption	50W		
Dimensions	380mm(L)X210mm(W)X190mm(H)		
Weight	4.5kg		
<b>CP-30 Fixed Focus Type</b>			
Projection distance	2~7m		
Projection magnification	21.5 x (at 5m)		
Projection size	267mmX267mm (at 5m)		
<b>CP-30Z Variable Focus Type</b>			
Variable focus refracting distance	Projection distance		
2M	1.6m~2.4m		
3M	2.3m~3.5m		
4M	3.0m~4.7m		
5M	3.7m~5.8m		
6M	4.4m~7.0m		
7M	5.1m~8.1m		

### STANDARD ACCESSORIES

REMOTE CONTROL, UM-4 BATTERIES

SCREEN FRAME (SIZE 379X379MM)

SPARE LAMP (12V AND 30W HALOGEN LAMP

SPARE FUSE (125V, 2A), TEST CHART CARD

### OPTIONAL ACCESSORIES

FLOOR STAND, WALL MOUNT BRACKET

